

DuraVinyl 352 Graphic Film

6-mil matte white semi rigid vinyl featuring an ultra low peel removable adhesive that is designed for wall graphics, point-of-purchase displays, decals, window decals, and other identification pieces.

Minimum Application Temperature

50°F



Temperature Ranges

-40°F to 180°F

- CAN BE REMOVED AND REPOSITIONED EASILY

6 mil Matte Semi Rigid Vinyl
Ultra Low Peel Adhesive

■ Premium White

QUICK ORDER

Option:

1 2 3 4

Qty Needed:

SHIP TO:

REPOSITION-ABLE DOOR DECAL ORDER FORM with CARE AND INSTRUCTIONS

Application Techniques

The surface must be clean, smooth, and as close to room temperature as possible. Before applying, prep area by cleaning with isopropyl alcohol or a mild soap solution and a lint free cloth. Decals should be applied dry. Use a roller to smooth the decal onto the substrate.

Expected Exterior Exposure

This product may be used for applications to exterior glass, up to 4 years. Temperature and weather may also limit the life of vinyl to exterior windows. Replace as needed.

Standard Decal Size: 12" x 12"

Custom Decal Size: w" x h"

Standard Color: Red (185) with White Copy

Custom PMS Color

1 English Only; Circle

2 Social Distancing; Square



3 English & Spanish; Square

4 Stop Sign

